



Fino Claro (Semi-translucent Smooth Finish)

Description

Fino Claro is a 100% Acrylic Polymer Based, semi translucent, crack resistant, smooth, trowel applied plaster finish.

Uses

Fino Claro may be used for either interior or exterior applications over properly prepared substrates, including new or properly prepared existing drywall.

Packaging

2.0 Gallon (22 lb) pail
1.0 Gallon (11 lb) pail

Colors

24 Standard colors

Custom colors available upon request.

Coverage

400-500 square feet
(20-24 m sq) per 2.0 Gal pail

VOC less than 40 g/L

Surface Preparation

Surface must be clean, dry, sound and free of loose material, releasing agents, efflorescence and other coatings. Remove and repair any loose paint, mortar, stucco or concrete. Repair all cracks with a patching compound and prime the entire surface prior to application to avoid telegraphing lines appearing through the dried finish. Wall surface should be flat and smooth before application of Fino Claro.

Mixing

Thoroughly mix the factory-prepared Fino Claro with a mixer to a homogeneous consistency. A small amount of clean, potable water may be added to adjust workability. When adding colorant packages in the field, mix thoroughly to completely disperse all colorant. Check color against color sample for accurate match. Close container when not in use. Clean tools with water immediately after use.

Application

Fino Claro may be applied over finished and primed level 4 drywall or over a base coat of either Fino Solido or Fino Alto. Apply with a stainless steel trowel, for best results Venetian trowels are recommended. Apply at approximately 1/64". Trowel in a random manner, using no straight vertical or horizontal trowel strokes. Trowel smooth to achieve minimal trowel marks and a slick finish. When stopping application of Fino Claro with out finishing a wall, feather the finish to a minimal thickness in an irregular line to prevent a cold joint from forming when application is resumed.

Drying Time

Fino Claro will generally dry within one hour. Surface absorption, temperature and humidity affect drying time

Shelf Life

Minimum of one year when stored in a cool dry location out of direct sunlight and kept from freezing.

Technical Data

- VOC content: <20 grams per liter
- Surface Burning Characteristics ASTM E 84:
 - Class A
 - Flame Spread Index: 20
 - Smoke Developed Index: 5
- Mildew and Mold Resistance - ASTM D 3273:
 - 9 - 10
- Water Vapor Transmission - ASTM D 1653:
 - 23.9 perms