

MATERIAL SAFETY DATA SHEET

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Variance/VariPrime VARIANCE FINISHES
 DATE PRINTED: 3/28/00

MANUFACTURER:
 ULTRAKOTE PRODUCTS, INC.
 327 South 27th Avenue
 Phoenix, AZ 85009

EMERGENCY TELEPHONE: (800-424-9300) CHEMTREC

PREPARER: Anthony Skelhorn, PHONE: (800)224-2344 PREPARE DATE: 3/28/00

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT% LESS THAN
01	Limestone, Calcium Carbonate	1317-65-3	20.0%
02	TiO ₂	13463-67-7	15.0%
03	Kaolin	1332-58-07	10.0%
04	Propylene Glycol	57-55-6	5.0%

ITEM	EXPOSURE LIMITS					
	ACGIH		OSHA		COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	10 mg/m ³	N.E.	15 mg/m ³	N.E.	N.E.	NO
02	10 mg/m ³	N.E.	15 mg/m ³	N.E.	N.E.	NO
03	2 mg/m ³	N.E.	15 mg/m ³	N.E.	N.E.	NO
04	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

SECTION 3 – HAZARDOUS IDENTIFICATION

EFFECTS OF OVEREXPOSURE – EYE CONTACT: May cause slight irritation.

EFFECTS OF OVEREXPOSURE – SKIN CONTACT: Substance may cause slight skin irritation.

EFFECTS OF OVEREXPOSURE – INHALATION: May cause respiratory tract irritation.

(Continued on Page 2)

SECTION 3 – HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE – INGESTION: Irritating to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE – CHRONIC HAZARDS: No known components of this product are listed as known or suspected carcinogens per NIOSH, NTP, IARC, or OSHA. Preexisting respiratory or skin condition (s) may be aggravated by exposure.

PRIMARY ROUTE (S) OF ENTRY: SKIN CONTACT, INHALATION, EYE CONTACT

SECTION 4 – FIRST AID MEASURES

FIRST AID – EYE CONTACT: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID – SKIN CONTACT: Remove contaminated clothing and shoes. Wash affected area(s) thoroughly with soap and water. If irritation persists, seek medical attention.

FIRST AID – INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID – INGESTION: If swallowed, DO NOT induce vomiting. Give victim one glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomit into lungs.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: 210* f

LOWER EXPLOSIVE LIMIT: 0.0%

UPPER EXPLOSIVE LIMIT: 0.0%

AUTOIGNITION TEMPERATURE: N.D.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL ALCOHOL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information.

SPECIAL FIREFIGHTING PROCEDURES: Containers exposed to fire should be kept cool with water spray. As in any fire, wear self contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

(Continued on Page 3)

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat absorbent/sweep cycle until all the spill has dried up. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 – HANDLING AND STORAGE

HANDLING: Use only in a well ventilated area. Keep out of reach of children.

STORAGE: Keep container closed when not in use.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Wear gloves (Natural, supported PVC, neoprene, or nitrile rubber), eye goggles, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGENIC PRACTICES: Do not take internally. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	= 364 -374* f	VAPOR DENSITY	= Is heavier than air
ODOR	= Mild Acrylic	ODOR THRESHOLD	= N.D.
APPEARANCE	= Liquid	EVAPORATION RATE	= Less than 1 (Ether=1)
SOLUBILITY IN H2O	= Appreciable		
PERCENT VOLITILE	= 50 +%	SPECIFIC GRAVITY	=1.405 – 1.445
VAPOR PRESSURE	= Approx 17mmHg	pH @ 100.0%	= 10.0 – 11.0s.u.
VISCOSITY	= N.D.		
PHYSICAL STATE	= Liquid		

(See Section 16 for abbreviation legend)

(Continued on Page 4)

SECTION 10 – STABILITY AND REACTIVITY

CONDITIONS TO AVOID: No Information.

INCOMPATIBILITY: Avoid contact with strong oxidizing agents and acidic agents, strong Lewis or mineral acids.

HAZARDS DECOMPOSITION PRODUCTS: Smoke may be acrid and the fumes irritating. Burning generates CO, CO2 and smoke. Product is not an Oxygen donor.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 – TOXICOLOGICAL PROPERTIES

PRODUCT DERMAL LD50: No Information. PRODUCT ORAL LD50: No Information.

PRODUCT LC50: No Information.

COMPONENT TOXICOLOGICAL INFORMATION:

-----CHEMICAL NAME-----	DERMAL LD50-----	ORAL LD50-----	LC50-----
Limestone, Calcium Carb	No Information	6450 mg/kg	No Information
TiO2	No Information	7500 mg/kg	No Information
Propylene Glycol	18500 mg/kg	20 g/kg	No Information
Kaolin	No Information	590 mg/kg	No Information

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Review all local, state, and federal regulations concerning health and pollution for appropriate disposal procedures.

SECTION 14 – TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not Regulated.

DOT TECHNICAL NAME: N.A.

DOT HAZARD CLASS: N.A.

HAZARD SUBCLASS: N.A.

DOT UN/NA NUMBER: N.A.

PACKING GROUP: N.A. RESP. GUIDE PAGE:

DOT PLACARD AT: N.A.

(Continued on Page 5)

SECTION 14 – TRANSPORTATION INFORMATION

DOT CLASS NUMBER: N.A.

UN PROPER SHIPPING NAME: Not Regulated.

UN HAZARD CLASS: N.A.

UN CLASS NUMBER: AIR N.A. MARINE: N.A.

HAZARD SUBCLASS: AIR N.A. MARINE: N.A.

UN UN/NA NUMBER: N.A.

UN PACKING GROUP: AIR N.A. MARINE: N.A.

UN PLACARD AT: N.A.

SECTION 15 – REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS-

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910, 1200)

CERCLA – SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA ‘Hazard Categories’ promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

-----CHEMICAL NAME-----CAS NUMBER -----WT/WT % IS LESS THAN

No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

----- CHEMICAL NAME-----CAS NUMBER

No Information is available.

U.S. STATE REGULATIONS: AS FOLLOWS –

SECTION 15 – REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65:

WARNING: The chemical (s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

-----CHEMICAL NAME-----CAS NUMBER

INTERNATIONAL REGULATIONS: AS FOLLOWS –

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS: No information available

SECTION 16 – OTHER INFORMATION

HMIS RATINGS – HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0

PERSONAL PROTECTION: B

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.26 lbs/gal, 31.63 grams/ltr

LEGEND: N.A. – Not Applicable, N.E.- Not Established
N.D. – Not Determined

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of UltraKote’s knowledge, or is obtained from sources believed by UltraKote to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. UltraKote assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, UltraKote assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

<END OF MSDS>